

VOLKSWAGEN (VW) (EU) GOLF V 1K1

GOLF V 1.6 16V FSI (2003-2008)



ENGINE BAG, BLF, BLP
Capacity: 3,5 liter

USE Extended drain (max)	CLIMATE Moderate
------------------------------------	----------------------------

PRODUCT RECOMMENDATION 1 SynGold LL-III Premium 0W-30	PRODUCT RECOMMENDATION 2 SynGold LL-III Premium 5W-30	PRODUCT RECOMMENDATION 3 SynGold LL-III Plus 5W-30
------------------------------------------------------------------------	------------------------------------------------------------------------	---------------------------------------------------------------------

Change every 30000 km/ 24 months

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 SynGold LL-III Premium 0W-30	PRODUCT RECOMMENDATION 2 SynGold LL-III Premium 5W-30	PRODUCT RECOMMENDATION 3 SynGold LL-III Plus 5W-30
------------------------------------------------------------------------	------------------------------------------------------------------------	---------------------------------------------------------------------

Change every 15000 km/ 12 months

USE Normal	CLIMATE Cold
----------------------	------------------------

PRODUCT RECOMMENDATION 1 SynGold 5W-30		
---------------------------------------------------------	--	--

Change every 15000 km/ 12 months

TRANSAXLE AUTOMATIC 09G 6/1
Capacity: 7 liter (Initial fill)

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 SynMulti ATF 5+		
-----------------------------------------------------------	--	--

Check every 48 months/ 60000 km

TRANSAXLE MANUAL 0AG 6/1
Capacity: 2 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 SynTrag Multi MTF 75W-80	PRODUCT RECOMMENDATION 2 Hypoid GL-4/GL-5 75W	
--------------------------------------------------------------------	----------------------------------------------------------------	--

Check every 48 months/ 60000 km

VOLKSWAGEN (VW) (EU) GOLF V 1K1

GOLF V 1.6 16V FSI (2003-2008)



HYDRAULIC BRAKE/CLUTCH SYSTEM ABS
Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Brake Fluid Super LV DOT 4		

Change every 24 months

COOLING SYSTEM
Capacity: 5,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.